







Crackling-free XLR-OBS sockets, are the newest achievement of Rduch company. Thanks to these sockets, crackling noises are eliminated from the completed sound systems. The device is powered by phantom power. For the sockets to work properly, the XLR housing must be connected with his own ground connection (XLR connector)

Technical data	XLR-OBSx1	XLR-OBSx2
Version	plastic + aluminum	plastic + aluminum
Phantom power [V]	24 - 48	24 - 48
Number of XLR sockets	1	2
Application	on plaster	on plaster
Dimensions [mm]	82/82/40	82/82/40
Weight [g]	90	95

Sockets XLR	XLR-OBSx1		XLR-OBSx2	
				
Technical data	XLR-OBx1	XLR-OBx2	XLR-PTx1	XLR-PTx2
Version	plastic + aluminum	plastic + aluminum	plastic + aluminum	plastic + aluminum
Application	Application of the microphone cable to the XLR-OBS socket	Application of the microphone cable to the XLR-OBS socket	under plaster	under plaster
Number of XLR sockets	1	2	1	2
Dimensions [mm]	82/82/40	82/82/40	82/82/40	82/82/40
Weight [g]	90	105	80	90

NEW!

		
Technical data	OB-1	OB-2
Version	aluminum	aluminum
Application	on plaster	on plaster
Number of XLR sockets	1	2
Dimensions [mm]	50/71/33	50/71/33
Weight [g]	90	100