



*MEGw-LED electret microphones are discreet in appearance and provide high-quality sound for applications such as temples, courtrooms and conference sound systems. The MEGw-LED microphones are equipped with 12 SMD LEDs. Diodes provide illumination of a given letter or book. They are made in black or matt chrome - powder coated.*

Technical data	MEG-LED/45	MEG-LED/50	MEG-LED/55	MEG-LED/60	MEG-LED/65	MEG-LED/70	MEG-LED/75
Frequency response	30Hz - 18kHz	30Hz - 18kHz	30Hz - 18kHz	30Hz - 18kHz	30Hz - 18kHz	30Hz - 18kHz	30Hz - 18kHz
Sensitivity (1kHz)	15 mV/Pa	15 mV/Pa	15 mV/Pa	15 mV/Pa	15 mV/Pa	15 mV/Pa	15 mV/Pa
Impedance	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω
Characteristics	hypercardioid	hypercardioid	hypercardioid	hypercardioid	hypercardioid	hypercardioid	hypercardioid
Signal/noise ratio (S/N)	66 dB	66 dB	66 dB	66 dB	66 dB	66 dB	66 dB
Max. sound level for 0.5% THD (SPL)	120 dB	120 dB	120 dB	120 dB	120 dB	120 dB	120 dB
Phantom voltage	20 - 48 V DC	20 - 48 V DC	20 - 48 V DC	20 - 48 V DC	20 - 48 V DC	20 - 48 V DC	20 - 48 V DC
Cable length	5 m	5 m	5 m	5 m	5 m	5 m	5 m
Microphone length (mm)	400	450	500	550	600	650	700
Weight (g)	400g	410g	420g	430g	440g	450g	460g