



MEG-Pp electret microphones on a flexible arm have an aesthetic appearance, they are placed on a stand with a button. They suppress feedback well and have a hypercardioid characteristic. They guarantee very good sound quality and speech understanding. They are available in black.

Technical data	MEG-Pp/40	MEG-Pp/45	MEG-Pp/50	MEG-Pp/55	MEG-Pp/60	MEG-Pp/65	MEG-Pp/70
Frequency response	30Hz - 18kHz	30Hz - 18kHz	30Hz - 18kHz	30Hz - 18kHz	30Hz - 18kHz	30Hz - 18kHz	30Hz - 18kHz
Sensitivity (1kHz)	15 mV/Pa	15 mV/Pa	15 mV/Pa	15 mV/Pa	15 mV/Pa	15 mV/Pa	15 mV/Pa
Impedance	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω
Characteristics	hypercardioid	hypercardioid	hypercardioid	hypercardioid	hypercardioid	hypercardioid	hypercardioid
Signal/noise ratio (S/N)	66 dB	66 dB	66 dB	66 dB	66 dB	66 dB	66 dB
Max. sound level for 0.5% THD (SPL)	120 dB	120 dB	120 dB	120 dB	120 dB	120 dB	120 dB
Phantom voltage	20 - 48 V DC	20 - 48 V DC	20 - 48 V DC	20 - 48 V DC	20 - 48 V DC	20 - 48 V DC	20 - 48 V DC
Cable length	5 m	5 m	5 m	5 m	5 m	5 m	5 m
Microphone length (mm)	40	45	50	55	60	65	70

Microphone frequency characteristics MEG-Pp