



The MEGzw-15 type electret microphones have a discreet design, providing high-quality sound in applications such as public address systems for temples, courtrooms and conference rooms. They are made in black or matt chrome - powder coated.

Technical data	MEGzw-15/45	MEGzw-15/50	MEGzw-15/55	MEGzw-15/60	MEGzw-15/65	MEGzw-15/70	MEGzw-15/75
Frequency response	30Hz- 20kHz	30Hz- 20kHz	30Hz- 20kHz	30Hz- 20kHz	30Hz- 20kHz	30Hz- 20kHz	30Hz- 20kHz
Sensitivity (1kHz)	16 mV/Pa	16 mV/Pa	16 mV/Pa	16 mV/Pa	16 mV/Pa	16 mV/Pa	16 mV/Pa
Impedance	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω	200 Ω
Characteristics	hypercardioid	hypercardioid	hypercardioid	hypercardioid	hypercardioid	hypercardioid	hypercardioid
Phantom voltage	20 - 52V DC	20 - 52V DC	20 - 52V DC	20 - 52V DC	20 - 52V DC	20 - 52V DC	20 - 52V DC
Signal/noise ratio (S/N)	66 dB	66 dB	66 dB	66 dB	66 dB	66 dB	66 dB
Max. sound level for 0.5% THD (SPL)	120 dB	120 dB	120 dB	120 dB	120 dB	120 dB	120 dB
Cable length	5m	5m	5m	5m	5m	5m	5m
Microphone length	45 cm	50 cm	55 cm	60 cm	65 cm	70 cm	75 cm
Weight	400 g	410 g	420 g	430 g	440 g	450 g	460 g

Frequency characteristics of the MEGzw-15 microphone